

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 December 2000 (14.12.2000)

PCT

(10) International Publication Number
WO 00/75878 A1

(51) International Patent Classification⁷: G07C 1/30,
B60R 13/10

(21) International Application Number: PCT/DK00/00306

(22) International Filing Date: 7 June 2000 (07.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 1999 00808 8 June 1999 (08.06.1999) DK

(71) Applicant and

(72) Inventor: HØJ, Maryan [DK/DK]; Pile Allé 9.3.1,
DK-2000 Frederiksberg (DK).

(74) Agent: PATENTGRUPPEN APS; Arosgaarden,
Aaboulevarden 23, DK-8000 Aarhus C (DK).

(81) Designated States (*national*): AE, AL, AM, AT, AT (util-
ity model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN,

CR, CU, CZ, CZ (utility model), DE, DE (utility model),
DK, DK (utility model), DM, EE, EE (utility model), ES,
FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT,
LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL,
PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL,
TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR DISPLAYING THE TIME OF PARKING OF A VEHICLE



(57) Abstract: The present invention relates to a device for displaying the time of parking of a vehicle by placing the device on the front screen of the vehicle, said device comprising display means which receives a timer signal from a time signal generation means via control means, said control means being connected to the ignition system of the vehicle in such a way that an update of the time display is frozen once the ignition of the vehicle is turned off, said control means being adapted to receiving the time signal from an external signal generation means. By a device according to the present invention, the displayed time in the vehicle containing the device when parked is reliable as far as the time of parking is concerned since the time signal is received from an external source and can therefore not be manipulated before being displayed.

WO 00/75878 A1

DEVICE FOR DISPLAYING THE TIME OF PARKING OF A VEHICLE

The present invention relates to a device for displaying the time of parking of a vehicle by placing the device on the screen of the vehicle.

5

Especially in some urban areas with parking regulations, the driver of a vehicle is obliged to use a parking discs to display the time of parking when parking the vehicle in parking areas with a parking time limit. For this purpose, parking discs are used. The parking disc is usually placed in the upper or lower corner the front screen in
10 such a way that it is clearly visible from the outside. The parking disc comprises a dial with the face of a clock and a hand that is manually set by the driver of the vehicle at the time of parking.

It has been known to happen that a driver forgets to set the parking disc which may
15 result in a parking fine to the driver or owner of the vehicle. In order to overcome this risk, various ideas have been exercised in order to provide an automatic system for setting the parking time of the vehicle. The automatic time displaying device typically comprises display means which receives a timer signal from time signal generation means via control means, said control means being connected to the
20 ignition system of the vehicle in such a way that the update of the time display is frozen once the ignition of the vehicle is turned off.

However, these automatic systems involve some serious drawbacks and have not been allowed by traffic and/or parking authorities so far. A problem with the known
25 devices for automatically displaying the time of parking is that the systems are not tamper proof. In order to allow parking displaying devices, the authorities must have a guarantee that the displayed time reflects the actual time of parking.

It is the object of the present invention to provide a device for displaying the parking
30 time of a vehicle which cannot be tampered with by the driver, thus ensuring that the parking time displayed reflects the actual time of parking.

CONFIRMATION COPY

This object is achieved by a device for displaying the time of parking of a vehicle by placing the device on the screen of the vehicle, said device comprising display means which receives a timer signal from a time signal generation means via control means, said control means being connected to the ignition system of the vehicle in such a way that the update of the time display is frozen once the ignition of the vehicle is turned off, and in such a way that the control means are adapted to receiving the time signal from an external signal generation means.

By a device according to the present invention, the displayed time at which the vehicle containing the device is parked is reliable as far as the time of parking is concerned since the time signal is received from an external source and can therefore not be manipulated before being displayed. By using an external time signal representing the actual present time, a device according to the invention is automatically adjusted in accordance with the actual time zone which the vehicle is in, i.e. change between summer and winter time is automatically adjusted. Moreover, the device may also be adapted to receiving position related data, so that an adjustment of the displayed time may automatically be made if the vehicle enters a new time zone. A device according to the invention thus provides as a fully automatic device for displaying the time of parking whereby the risk of forgetting to the set parking time is eliminated.

As long as the ignition is on and the engine is running, the externally generated time signal updates the display via the control means so that the time shown on the display reflects the present time in hours and minutes. Once the ignition is turned off, the time on the display will be "frozen", so that the time displayed reflects the time when the ignition was turned off. This time corresponds to the time of parking of the vehicle.

The external time signal source could preferably be a radio signal transmitted from a radio or satellite transmitter, such as the known central time signal generators transmitting the time signal generated by an atomic clock to various other time displaying means, e.g. watches, etc. Other time signal sources could be satellites used

for GPS navigation. The time signals as well as the position data from such sources cannot be manipulated due to the nature of the signal generation.

5 Preferably, the control means comprises an antenna for receiving an external time signal which feeds the received signal to a receiver provided with one or more crystals, and a microprocessor that receives a digitized time signal from the receiver and updates the display means in accordance with collected data of the ignition state and the execution of an operation program. The antenna, the receiver and the crystals are designed in accordance with the specific time signal to be received. The control
10 means may be compact in design so that the device may be hidden behind a panel or the like in a vehicle.

The microprocessor may also include a memory for storing the time for updating the display means at a pre-determined time interval as long as the ignition of the vehicle
15 is on and then updating the display again after the ignition has been turned off. Hereby, the device may be fully automatic so that the device is immediately ready again after having been in a parked state. The pre-determined time interval is initially set in accordance with regulative requirements, such as 15 minutes.

20 A manually operated switch may be provided in connection with the microprocessor in order to allow for adjustment of the time of parking manually. Hereby, the device may be manually operated e.g. if the vehicle is parked in between two updates or if the device is not capable of receiving a time signal, e.g. if the external source is out of order.

25

In the preferred embodiment, the display means comprises an LCD display with a translucent or transparent background. Hereby, the device blends in with the surroundings and does only block a minor part of the front screen visually.

30 The display means preferably comprises both an outwardly and an inwardly facing display making it easy to check if the display is correctly set when the car is parked.

In a preferred embodiment, at least one display, preferably the outwardly facing display, is a clock dial. This design involves graphic representation of time and makes it easy for a parking officer to visually check the time of arrival in the parking slot.

5

The inwardly facing display may preferably be an LCD display with four digits separated in pairs of two. This type of display facilitates checking of the time from inside the car and makes it easy to determine if an adjustment of the "frozen" time in the display is required before vacating the car.

10

As an additional aspect of the above-mentioned embodiments, the device may also receive a data signal representing the position of the vehicle, and may be provided with data transmitting means for collecting arrival and departure time data when entering and leaving a geographically defined zone and subsequently transmitting said data to a central recording unit. In this embodiment, a device according to the invention may record and display the time of arrival in the parking slot while also recording the duration of the parking and/or time of presence in a particular location. Thus, it becomes possible to make automatic recordings of the time of presence within e.g. a geographically defined zone, such as an urban area, in which a system of road pricing is in force. Moreover, via the central recording unit, automatic debiting of the road pricing and/or parking fees from the drivers or vehicle owner's bank account may be performed.

15
20

In the following, the invention is described in detail with reference to a preferred embodiment and to the accompanying figures, in which

25

fig. 1 shows a block diagram of the electrical implementation of a device according to a preferred embodiment of the invention, and

30 figs. 2 and 3 are schematic illustrations of LCD displays in the device.

The block diagram in fig. 1 shows an electrical implementation of a device according to the invention.

The device comprises a ferrite antenna 2 connected to a receiver 3 for receiving a time signal. The receiver 3 forwards the time signal to a microprocessor 5 that controls the display drivers 7, 8 connected to displays 9, 10 in accordance with control data from the peripheral connections 12.

Ferrite Antenna

The antenna 2 consists of a ferrite rod, a coil and a capacitor. The rod is approx. 6 cm long and the diameter is approx. 8mm. The coil is wound around the rod and the capacitor is mounted across the coil (connected in parallel). The value of the coil and the capacitor must be selected to provide a resonant frequency of 77.5KHz with a resonant resistance of 50Kohm to 200Kohm. A high Q-value is preferable in order to improve reception in noisy areas. However, a very high Q-value may cause a variation in the resonant frequency with temperature.

77.5 KHz Receiver

The receiver 3 is a standard chip implementing a straight-through receiver circuit in the frequency range of 40KHz to 80KHz. This chip is designed for radio-controlled clock application. The input for the receiver 3 is an amplitude modulated carrier-frequency. The modulation contains digitally coded information of the precise time, date and year. The output from the chip is a digitized serial signal containing raw information from the modulation. This signal is transferred to the microprocessor 5 for further processing.

The characteristics of the standard receiver chip are:

- Very low power consumption
- Very high sensitivity
- High selectivity
- Power-down mode
- Digitized serial output signal
- AGC hold mode

Crystal 77.5KHz

The standard receiver chip requires two crystals 4. However, if full sensitivity and selectivity are not required, one of these crystals may be substituted for a capacitor.

The specification for the crystals 4 is:

- Frequency : 77.5KHz
- Freq. Tol.: 20ppm
- Freq. stability over temp. 0.034ppm
- 10 • Operating temp -20 °C to 70°C
- Equivalent Series Resistance 50Kohm
- Load Capacitance 12.5pF

Voltage Regulator

15 This circuit consists of a standard series regulator 11. The input for the series regulator 11 is the battery voltage from the car. The output from the series regulator 11 is 3.3Volt which is the supply voltage for all electrical circuits. The requirements to the voltage regulator 11 are:

- Minimum Input Voltage: 7 Volt
- 20 • Maximum Input Voltage 15 Volt
- Output Voltage: 3,3 Volt +/- 10%
- Maximum Load Current: 50 mA.

Microprocessor

25 The microprocessor 5 is a low-cost 8 bit microcontroller. The MC68HC908 is selected. It includes 1.5K Flash, 128 bytes of flash, 2 x 16 timers, 15 general I/O pins and on board flash programming.

It will interface

- 30 • to the 77.5KHz receiver, 2 wire (interface)
- to the primary display driver, 3 wire (interface)
- to the secondary display driver, 3 wire (interface)

- to the ignition switch, 1 wire
- to the push button switch, 1 wire
- to a flash/debug interface, 3 wire (interface)

5 The application running on this processor 5 will then concurrently sample the time by readings from the receiver 3, and the recorded time will be written in primary and secondary displays 7, 8. By supervising the ignition state, and when in ignited state updating time on the displays 9, 10, a transition to non-ignited state will stop the display update. If the push button is activated in this state, the program must adjust
10 the displays forward by 15 minutes for each activation. When the ignition is turned on again, the current time will be outputted on the displays 9, 10.

If/when the power supply has been off or if the radio connection (to DFC77 transmitter) is lost, a frame synchronisation protocol to the DCF77 transmitter must
15 follow. Otherwise, the time at any state will be stored in the memory.

Primary Display Driver

The primary display driver 7 is represented by a standard LCD driver. It controls 2 backplane segments and 24 multiplexed segment inputs. Through a 3 wire serial
20 interface, it will be controlled by the processor. Included in this circuit is a temperature compensating passive component network in order to stabilise display contrast over temperature.

Secondary Display Driver

25 The second display driver 8 is represented by a standard LCD driver. It controls 1 backplane segments and 29 segment inputs. Through a 3 wire serial interface, it will be controlled by the processor. Included in this circuit is a temperature compensating passive component network in order to stabilise display contrast over temperature.

30 Front (Primary) LCD Display

The first display 9 is shown in fig. 2. It is a 48 segment custom-made LCD display with a circular watch vision with 10 cm of visible area. This display constitutes the

part of the display means of the time recording device which is visible from the outside of the vehicle.

5 The time "cursor" is an addressable segment on the display. Forty eight of these arrows are in fact available in the display LCD structure, thus providing a 15 minutes resolution. For that reason, they are placed in a circle whose origin is at the centre of the display. Hour digits/dashes are printed on the glass.

10 The display 9 is multiplexed 1:2, i.e. with 2 backplane segments and 24 segment inputs. It is driven by the Primary display driver. The connection from the display to the PCB (Printed circuit board) will be provided by elastomeric connectors connecting terminals on the LCD glass to PCB gold plated terminals.

Rear (Secondary) LCD Display

15 This second display 10 is shown in fig. 3. It is a 29 segment standard LCD display. Four 7 segment digits divided in pairs of two and separated by semicolons will show hours and minutes. The 2 first digits will show hours.

20 This display 10 is visible from the inside of the vehicle and is only used to control the primary display when manual setting of the primary display (by activating push button) is required. The 29 digits are addressable through areas in the LCD structure. The display is non-multiplexed, i.e. it has one backplane and the 29 segments must be driven statically. It is driven by the Secondary display driver. The connection from the display to the PCB will be provided by elastomeric connectors connecting
25 terminals on the LCD glass to the PCB gold plated terminals.

Push Button

In the preferred embodiment, the device is provided with a push-button 6. Once this button is activated, the time indicator on both displays advances 15 minutes. To
30 repeat this, the button 6 must be released and then pushed again. With this function, the time of arrival can be set manually.

Peripheral Connections

A small standard RJ-11 connector is implemented. This connector provides easy connection and disconnection between the device and the required peripheral wiring 12. The wiring must be turned off with an RJ11-plug.

5

The wiring requires the following three peripheral connections 12:

- 12 Volt from the car battery
- Chassis
- Ignition Switch

10

The input from the ignition switch is protected against electrical transients. The input tolerates signals up to 15Volts. The minimum voltage for detection of the ignition switch is 2.4Volt.

- 15 The device is capable of operating at temperatures ranging from -20°C to 70°C and may be stored at storage temperatures ranging from -30°C to 85°C

It is realised by the present invention that other components and implementive solutions than the above-mentioned may be used without departing from the scope of 20 the invention as defined by the accompanying claims.

PATENT CLAIMS:

1. A device for displaying the time of parking of a vehicle by placing the device on the screen of the vehicle, said device comprising
5 display means which receives a timer signal from a time signal generation means via control means,
said control means being connected to the ignition system of the vehicle in such a way that an update of the time display is frozen once the ignition of the vehicle is turned off,
10 characterised by
the control means being adapted to receiving the time signal from an external signal generation means.
2. A device according to claim 1, wherein the time signal is received from at least
15 one satellite.
3. A device according to claim 2, wherein the at least one satellite, from which the time signal is received, is also usable in a global positioning system (GPS) for providing positioning data of the vehicle.
20
4. A device according to claim 1, wherein the time signal is received via a radio transmitter.
5. A device according to any of claims 1 to 4, wherein the control means comprises
25 an antenna for receiving an external time signal which feeds the received signal to a receiver provided with one or more crystals, and a microprocessor which receives a digitized time signal from the receiver and updates the display means of the ignition state in accordance with collected data.
- 30 6. A device according to claim 5, wherein the microprocessor includes a memory for storing the time for updating the display means at a pre-determined time interval as

long as the ignition of the vehicle is on and subsequently updates the display after the ignition has been turned off and then turned back on again.

5 7. A device according to claim 5 or 6, wherein a manually operated switch is interfaced with the microprocessor in order to allow setting of the time of parking manually.

10 8. A device according to any of the preceding claims, wherein the display means comprises an LCD display with a translucent or transparent background.

9. A device according to any of the preceding claims, wherein the display means comprises an outwardly and an inwardly facing display.




15 10. A device according to claim 9, wherein at least one display, preferably the outwardly facing display, is a clock dial.

11. A device according to claim 9 or 10, wherein the inwardly facing display is an LCD display with four digits separated in pairs of two.

20 12. A device according to any of the preceding claims, wherein a data signal representing the position of the vehicle is received, and wherein the data transmitting means are provided for collecting arrival and departure time data when entering and leaving a geographically defined zone which transmits said data to a central recording unit.

25 13. A device according to claim 12, wherein the data transmitted by the data transmitting means additionally or alternatively comprises information, such as an SMS message, to a dedicated mobile communication device about the vehicle in order for the user of said communication device to monitor the duration of the
30 parking time of the vehicle.

1/1

*Fig. 1**Fig. 2**Fig. 3*

INTERNATIONAL SEARCH REPORT

International Application No

PC 1/D 9/00306

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G07C1/30 B60R13/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G07C B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 296 07 726 U (HAGEMANN H ET AL) 14 August 1996 (1996-08-14) the whole document	1,2,4,6
Y	---	3
X	DE 91 07 902 A (REHAU AG & CO) 14 August 1991 (1991-08-14) page 2 -page 5	1,4,6,8
Y	---	3
Y	WO 94 16396 A (AT/COMM INCORPORATED) 21 July 1994 (1994-07-21) page 5 -page 8; figures 1,3	3
X	DE 40 13 719 A (GERLING H) 31 October 1991 (1991-10-31) the whole document	1

	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

15 September 2000

Date of mailing of the international search report

06. 11. 00

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Inger Löfving

INTERNATIONAL SEARCH REPORT

International Application No

PC/00306

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 295 11 185 U (KASEL A) 26 October 1995 (1995-10-26) the whole document ---	1
X	WO 94 28517 A (WANDSCHNEIDER) 8 December 1994 (1994-12-08) page 4 -page 7; figures 1-4 ---	1,4,5
P,Y	WO 99 34338 A (VIJAYAKUMAR J) 8 July 1999 (1999-07-08) page 3 -page 6 ---	3
A	DE 196 21 424 A (TELEMEDIA GMBH) 4 December 1997 (1997-12-04) the whole document -----	1-13

INTERNATIONAL SEARCH REPORT

International patent family members

International Application No

PCT/DK/93/00306

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 29607726 U	14-08-1996	NONE	
DE 9107902 A		NONE	
WO 9416396 A	21-07-1994	US 5351187 A AU 5952794 A	27-09-1994 15-08-1994
DE 4013719 A	31-10-1991	NONE	
DE 29511185 U	26-10-1995	DE 19626948 A	16-01-1997
WO 9428517 A	08-12-1994	DE 4319224 A DE 4334248 A DE 9308888 U EP 0701724 A US 5687076 A DE 4420547 A DE 9409485 U	08-12-1994 13-04-1995 02-12-1993 20-03-1996 11-11-1997 05-01-1995 17-11-1994
WO 9934338 A	08-07-1999	DE 19757462 A	24-06-1999
DE 19621424 A	04-12-1997	NONE	